

Leichtlauf Performance 0W-20**Description**

Low-friction motor oil for year-round use. Guarantees reliable lubrication, minimizes wear and keeps the engine clean. Guarantees excellent performance with low fuel consumption. Ideally suited for engines with start/stop system.

Properties

- excellent wear resistance
- high lubrication reliability
- saves fuel and reduces pollutant emissions
- good ageing stability
- outstanding engine cleanliness
- tested for turbochargers and catalytic converters

Specifications / Approvals

ACEA C5, C6 • API SP

Technical data

SAE class (engine oils)	0W-20 SAE J 300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	42,0 mm ² /s ASTM D7042
Viscosity at 100 °C	8,1 mm ² /s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	13,0 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592
Total base number	8,0 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049
Oil base	Advanced Full Synthetic

European, Asian and American vehicles that stipulate lubricants that meet general specifications.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21883 BOOKLET
4 l Canister plastic	21887 BOOKLET
5 l Canister plastic	21884 BOOKLET
205 l Black plate barrel	21886 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

For gasoline, diesel and hybrid engines. Especially for