



# Shell Helix *Extra ECT Multi 5W-30*

*Fully synthetic motor oil - Enhance your engine's efficiency by reducing friction for optimized performance*

Shell Helix Extra ECT Multi 5W-30 uses Anti-Friction Technology that helps to reduce engine frictions to provide enhanced fuel economy and protection. With advanced emissions-compatible technology, it helps to keep diesel particulate filters clean to help maintain engine performance.

## DESIGNED TO MEET CHALLENGES

### Main Applications

- Shell Helix Extra ECT Multi 5W-30 fully synthetic motor oil uses Shell's advanced emissions-compatible technology to help protect the vehicle's emission system. Its low-SAPs formulation helps to keep diesel particulate filters clean and protects them from ash build-up that can block the exhaust system and lead to reduced engine performance.
- Shell Helix Extra ECT Multi 5W-30 can be used for modern gasoline engines, diesel engines with particulate filters and gas engines.

### Specifications, Approvals & Recommendations

- API SN
- ACEA C3
- VW 504.00/507.00
- MB-Approval 229.31/229.51
- meets the requirement of BMW LL-04

To find the right Shell Helix product for your vehicles and equipment, please consult Shell Lubematch at: <http://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

### Typical Physical Characteristics

| Properties          |        |                   | Method     | Shell Helix Extra ECT Multi 5W-30 |
|---------------------|--------|-------------------|------------|-----------------------------------|
| Density             | @15°C  | kg/m <sup>3</sup> | ASTM D4052 | 836                               |
| Kinematic Viscosity | @40°C  | cSt               | ASTM D445  | 69                                |
| Kinematic Viscosity | @100°C | cSt               | ASTM D445  | 12.11                             |
| Flash Point         |        | °C                | ASTM D92   | 238                               |
| Pour Point          |        | °C                | ASTM D97   | -45                               |

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Health, Safety & Environment

#### • Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet (SDS), which can be obtained from <https://www.epc.shell.com>

#### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.